According to Regulation (EC) No 1907/2006 amended by Regulation (EU) 2020/878

Page: 1

Compilation date: 01.02.2012

Revision date: 15.11.2023

Revision No: 5.3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Stein & Lino Stripp / Power Strip Product nr: 21022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Basic cleaner for professional users

1.3. Details of the supplier of the safety data sheet

Company name: Premiere Produkter AS

Austbøsletta 6, 4085 Hundvåg,

Tlf: +47 51 85 83 00,

Email: post@premiere-produkter.no

1.4. Emergency telephone number

Emergency tel: +47 22 59 13 00

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Eye Irrit. 2: H319

Most important adverse effects: Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Label elements under CLP:

Hazard statements: H315: Causes skin irritation.

H319: Causes serious eye irritation.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



Precautionary statements: P102: Keep out of reach of children.

P264: Wash hands thoroughly after handling.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+313: If eye irritation persists: Get medical advice.

Stein & Lino Stripp / Power Strip

Page: 2

P332+313: If skin irritation occurs: Get medical advice.

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-PHENOXYETHANOL - REACH registered number(s): 01-2119488943-21-0000

EINECS	CAS	SCL	CLP Classification	Percent
204-589-7	122-99-6	-	Acute Tox. 4: H302; Eye Irrit. 2: H319	5-10%
3-BUTOXYPRO	DPAN-2-OL			
225-878-4	5131-66-8	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315	5-10%
ISOTRIDECAN	IOL, ETHOXYLATI	ED - REACH registered number(s): 01-2	2119976362-32-0000	
500-241-6	69011-36-5	-	Eye Dam. 1: H318; Aquatic Chronic 3: H412	
2-BUTOXYETH	HANOL - REACH re	egistered number(s): 01-2119475108-3	6-0000	
203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	5-10%
2-(2-BUTOXYE	THOXY)ETHANO	L - REACH registered number(s): 01-21	19475104-44-0000	
203-961-6	112-34-5	-	Eye Irrit. 2: H319	5-10%
SODIUM CUM	ENESULPHONAT	E - REACH registered number(s): 01-21	19489411-37-0000	
239-854-6	15763-76-5	-	Eye Irrit. 2: H319	1-5%
2-AMINOETHA	NOL - REACH reg	istered number(s): 01-2119486455-28-	0000	
205-483-3	141-43-5	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302: Skin Corr. 1B: H314	1-<2%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. If conscious, give half a litre of water to drink immediately.

Consult a doctor.

Inhalation: Move affected person into fresh air. In case of respiratory tract irritation, consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Stein & Lino Stripp / Power Strip

Page: 3

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Not applicable.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Prevent the extinguishing

water into surface water or groundwater.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding

agents). Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from food, drink

and animal feedingstuffs. Storage class: 12 (Non-combustible liquids)

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): GISCODE: GG60

Stein & Lino Stripp / Power Strip

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-PHENOXYETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	110 mg/m3	110 mg/m3	-	-
2-BUTOXYETH	HANOL			
UK	25 ppm	50 ppm	-	-
2-(2-BUTOXYE	ETHOXY)ETHANOL			
UK	67.5 mg/m3	101.2 mg/m3	-	-
2-AMINOETHA	ANOL			

7.6 mg/m3

8.2. Exposure controls

UK

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

2.5 mg/m3

Hand protection: Protective gloves. Suitable material: NR (natural rubber), CR (polychloroprene) or NBR (nitrile

rubber), category III according to EN 374. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Breakthrough time (maximal wear duration): Wear duration with occasional contact, splashes (Level 2: < 30 min): Disposable-gloves,

Thickness of the material 0,1mm. Wear duration with permanent contact (Level 6: < 480min): Protective gloves, Thickness of the glove material 0,7 mm. Breakthrough times and swelling

properties of the material must be taken into consideration.

Eye protection: Safety glasses with side-shields. Ensure eye bath is to hand.

Skin protection: Not applicable.

Environmental: No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colourless

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Viscosity: Non-viscous

Boiling point/range°C: No data available. Melting point/range°C: Not applicable.

Flammability limits %: lower: No data available. [cont...]

Stein & Lino Stripp / Power Strip

Page: 5

upper: No data available.

Flash point°C: No data available. Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 1,007 g/ml pH: 11

VOC g/I: 31%

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: No hazardous decomposition products if stored and handled as prescribed.

10.5. Incompatible materials

Materials to avoid: None known

10.6. Hazardous decomposition products

Haz. decomp. products: No hazardous decomposition products known.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-PHENOXYETHANOL

ORL	MUS	LD50	933	mg/kg
ORL	RAT	LD50	1260	mg/kg
SKN	RAT	LD50	14422	mg/kg

3-BUTOXYPROPAN-2-OL

ORL	RAT	LD50	5660	μl/kg
SKN	RBT	LD50	3100	mg/kg

Stein & Lino Stripp / Power Strip

Page: 6

ISOTRIDECANOL, ETHOXYLATED

ORL	RAT	LD50	>2000	ma/ka
ONL	INAI	LDSU	/2000	IIIg/Kg

2-BUTOXYETHANOL

DERMAL	RBT	LD50	400	mg/kg
VAPOURS	RAT	4H LC50	1-5	mg/l

2-(2-BUTOXYETHOXY)ETHANOL

ORL	MUS	LD50	6050	mg/kg
ORL	RAT	LD50	4500	mg/kg

2-AMINOETHANOL

IVN	RAT	LD50	225	mg/kg
ORL	MUS	LD50	700	mg/kg
ORL	RAT	LD50	1720	mg/kg
SCU	RAT	LD50	1500	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

2-BUTOXYETHANOL

Daphnia magna	24H EC50	1800	mg/l
Oncorhynchus mykiss	96H LC50	1700	mg/l
Selenastrum capricornutum	72H EC50	911	mg/l

SODIUM CUMENESULPHONATE

Oncorhynchus mykiss	96H I C50	>100	ma/l
Official Hyriss	3011 LC30	/100	1119/1

12.2. Persistence and degradability

Persistence and degradability: The surfactant(s) contained in this preparation complies with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

Stein & Lino Stripp / Power Strip

Page: 7

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: no data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: The product has not been tested. Data apply to the components with the highest toxicological

risk.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Dispose of waste according to applicable local, state and federal regulations.

Disposal of packaging: May be reused following decontamination.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No.

1907/2006.

* indicates text in the SDS which has changed since the last revision.

Data references: Safety data sheets from our raw material suppliers

Department issuing MSDS: Product Development Department;

Contact: Ms. Tiemann, Ms. Klumpe

Classification for mixtures and used evaluation method according to Article 9 of regulation

(EC) 1272/2008 [CLP]:

Calculation method

Phrases used in s.2 and 3: H302: Harmful if swallowed.

H312: Harmful in contact with skin.

Stein & Lino Stripp / Power Strip

Page: 8

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.